VC5003G | 2G | SMS | WEB













We500 It's a flexible, autonomous and high performance 2G/3G wireless solution for remote monitoring, control and data logging systems.

ALL IN ONE...

The WE500 includes a GSM/GPRS or UMTS/HSPA modem, a built-in WEB server and a wireless remote monitoring and control system accessible through mobile device apps and PC browsers

• REMOTE MANAGEMENT

Control a system status remotely: modify set-points and change system configuration

MONITORING

Monitor a system status by continuously observing any changes that may occur over time

DATA LOGGING

Periodically record data and events of a system over time

IT'S... STANDALONE

Only a power source and a data enabled SIM card are needed to operate the device

IT'S... UNMANNED

No local interaction with a human operator is required

IT'S... WEB BASED

Device configuration and operation are totally web based using the built-in web server





VC5003G | 2G | SMS | WEB











ONE FOR ALL...

WE500 is the ideal solution for the remote monitoring, control and data logging in many fields such as:

Industrial application and M2M

Plant monitoring, control and data logging – Motors and pumps – Tanks, silos and storage facilities – Industrial cooling and refrigeration – Weather monitoring and telemetry – Physical access control – Vending machines

Water

Water leackage – Liquids level – Water treatment plants – Irrigation and greenhouse management – Hydroelectric power stations

Energy

Solar farms – Wind plants – Energy generators – Power supply control

Home and building automation

Heating and air-conditioning – Gates and windows opening systems – Lighting

Gas management

Wireless meter reading – Cathodic protection

TECHNICAL FEATURES


- 2 RS232 serial port on-board
- 1 RS485 serial port on-board
- 8 digital input (expandable)
- 2 digital output (expandable)
- 2 analog input (0-5V 0-10V 0-20mA / NTC, expandable)
- Modbus support: RTU and TCP
- Advanced alarms management
- Reliable data logging
- Data sending to the cloud
- Encrypted connectivity

NETWORKING AND STORAGE

- 3G UMTS/HSPA or 2G GSM/GPRS modem
- 10/100 Mbit/s RJ45 Ethernet

OPTIONAL ACCESSORIES AVAILABLE

- PS500 switch mode power supply for WE500
- UPS500 switch mode power supply with battery pack
- XP500 modbus I/O expansions
- Optional USB Host type A for expanded storage
- Optional WiFi and Bluetooth







Nethix s.r.l.

Via dei Pini, 21 31033 Castelfranco V.to (TV) - Italy T. +39 0423 770750 F. +39 0423 770749 info@nethix.com



nethix.com